

Revision Date: 04.16.25



DEL-VAL 310 WHITE ELASTOMERIC ROOF COATING

DESCRIPTION

Del-Val 310 White Elastomeric Roof Coating is an acrylic-based roof coating that forms a seamless, flexible layer of protection for your roof. Designed to seal, protect, and reduce the surface temperatures of the roof.

USES

This flexible coating is designed to protect a wide variety of substrates, including metal, BUR, APP, SBS Concrete, and EPDM. Once cured, Del-Val 310 provides a waterproof, durable, seamless, flexible weather resistant layer of protection.

PREPARATION

Surface must be free of all loose particles, dirt debris and other contaminants that could inhibit adhesion, pressure washing is recommended. A primer may be required for the particular substrate. Contact United Asphalt for more information.

APPLICATION

Apply by brush, medium nap roller or airless sprayer.

Airless spray: Minimum pump pressure 3000 psi.

Tip Size: .027"-.039" (.031" recommended)

Hose: Use 3/8" up to 100', from 100' to 200' use 1/2" or larger

SPECIFICATIONS

TOTAL SOLIDS BY VOLUME: ... 60% ± 2 ASTM D2697

WEIGHT SOLIDS: 70.10%

INITIAL PERCENT ELONGATION: 231.0%

INITIAL TENSILE STRENGTH: 118.3

PERMEANCE: 18.7 perms

COVERAGE

Apply at a minimum rate of 1 to 1.25 gallons per 100 square feet per coat, according to the substrate and condition. Two coats are recommended. A minimum of 16 mils DFT is recommended to achieve optimal performance of the coating. Normal drying time is 2-4 hours.

CLEANUP


Remove product from tools, etc., with kerosene or Del-Val Orange Cleaner & Degreaser. Clean hands with a waterless hand cleaner.

CODE APPROVALS/COMPLIANCE


Cool Roof Rated Product [PENDING]



TOOLS NEEDED ✓



PACKAGING SIZES ✓



LEARN MORE ↓

UnitedAsphalt.com/DV310

