

DEL-VAL 303 PREMIUM FIBERED ALUMINUM ROOFING COATING

DESCRIPTION

Del-Val 303 Premium Fibered Aluminum Roof Coating is a high performance coating that protects and extends the life of asphalt and metal roof surfaces. Formulated using selected asphalts and blended with high quality aluminum pigments with refined solvents and reinforcing fibers. Del-Val 303 Premium Fibered Aluminum Roof Coating's highly reflective surface protects the roof's surface from destructive overheating and actinic deterioration.

USES

Del-Val 303 is formulated for applications over new or existing built up roofs, APP, SBS, smooth or granulated surfaces, cap sheet and flashings. It can also be used for masonry surfaces and metal surfaces. DO NOT USE with EPDM, PVC, TPO or other single-ply membranes.

PREPARATION

Prepare the roof surface by sweeping clean any dust, dirt or debris. Use a wire brush to remove rust from metal. Roof surface must be oil-free and free of moisture both on and beneath the surface. Repair all holes, cracks, blisters, tears or breaks by spreading Del-Val 211 Flashing Cement over damaged area, then embed United Asphalt Cotton or Fiberglass Fabric. Allow repairs to cure 60 days before coating.

APPLICATION

Apply Del-Val 303 with a soft bristled brush, paint roller or heavy-duty spray equipment. Product should be mechanically mixed before applying. Spread the product uniformly over the roof surface. Work the coating in one direction. Do not work coating excessively during application as overworking the coating can have a damaging effect on the leafing of the aluminum.

COVERAGE

Apply at the rate of 1 to 1.5 gallons per 100 sq. ft.

CLEANUP

Clean tools with Del-Val Orange Cleaner & Degreaser, taking necessary precautions when handling combustible liquids.

CODE APPROVALS/COMPLIANCE

This product meets or exceeds the requirements of ASTM D-2824 Type III, and is Energy Star Approved and Cool Roof Rated





TOOLS NEEDED ~







PACKAGING SIZES ~





CERTIFICATIONS ~



